HUBER ENGINEERED MATERIALS

Safety Data Sheet

Hubercarb® Q2P

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03
Canadian Workplace Hazardous Material Information System (WHMIS) 2015
Mexico NOM-018-STPS-2000; NOM-018-STPS-2015
Globally Harmonized System (GHS)

Issue Date: 25/Apr/2019
Print Date: 26/Apr/2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name: Hubercarb® Q2P

Pure substance/mixture Substance

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Filler. Functional additive.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company:
Huber Carbonates, LLC
3100 Cumberland Boulevard, Suite 600
Atlanta, GA 30339 USA

Tel: +1 678 247-7300

Internet www.hubermaterials.com

E-mail hubermaterials@huber.com

1.4. Emergency telephone number CHEMTREC: +1 800 424 9300 or International +1 703 527 3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

OSHA Regulatory Status
Carcinogenicity category 1A
Specific target organ toxicity (STOT) - repeated exposure, category 2

GHS Classification
Carcinogenicity category 1A
Specific target organ toxicity (STOT) - repeated exposure, category 2

Physical Hazards	Not classified
Health Hazards	Carcinogenicity category 1A Specific target organ toxicity (STOT) - repeated exposure, category 2 Respiratory system
Environmental Hazard	Not classified

2.2. Label elements

Symbols/Pictograms



Signal Word	Danger
Hazard Statements	H350 - May cause cancer H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary Statements

Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust Wear protective gloves/protective clothing/eye protection/face protection
Response	IF exposed or concerned: Get medical advice/attention
Storage	Store locked up
Disposal	Dispose of contents/containers in accordance with local regulations

Additional Information: Not applicable.

Hazards not otherwise classified (HNOC) None known.

SECTION 3: Composition/information on ingredients

Pure substance/mixture Substance

Chemical Name	CAS Number	TSCA: United States	Canada (DSL)	Mexico	REACH registration number	OSHA Regulatory Status	WHMIS	Weight-%
Limestone	1317-65-3	Y	Y	Y	Exempt	Not classified	H350; H372	97 - 100
Crystalline Silica, quartz (impurity)	14808-60-7	Y	Y	Y	Exempt	Carcinogenicity category 1A Specific target organ toxicity (STOT) - repeated exposure, category 2	H350; H372	0.2 - 2

Legend
X / Y: Complies , - / N: Not Listed , Exempt

SECTION 4: First aid measures

4.1. Description of first aid measures

General Advice When in doubt or if symptoms are observed, get medical advice.

Eye Contact In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Skin Contact Wash with plenty of soap and water.

Ingestion Rinse mouth thoroughly with water.

Inhalation If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

Aspiration hazard Not an expected route of exposure.

4.2. Most important symptoms and effects, both acute and delayed Signs and symptoms may include coughing, gasping, choking and difficulty breathing.

4.3. Indication of any immediate medical attention and special treatment needed IF exposed or concerned: Get medical advice/attention. Treatment should be symptomatic and supportive. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media
Water spray (fog). Foam. Dry chemical. Carbon dioxide (CO2).

Unsuitable Extinguishing Media
None known.

5.2. Special hazards arising from the substance or mixture
Do not breathe dust.

5.3. Advice for firefighters

Special protective equipment for firefighters
Wear a self-contained breathing apparatus and chemical protective clothing.

Fire-fighting measures
In case of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	Keep unauthorized personnel away. Use personal protection recommended in Section 8. Avoid dust formation. Ensure adequate ventilation.
For non-emergency personnel	Keep unauthorized personnel away.
For emergency responders	Keep unauthorized personnel away. Use personal protection recommended in Section 8.
6.2. Environmental precautions	Avoid runoff to waterways and sewers.
6.3. Methods and material for containment and cleaning up	Large Spill: Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect dust Small Spill: Vacuum or sweep material and place in a disposal container
6.4. Reference to other sections	Section 8: Exposure controls and personal protection. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Avoid exposure - obtain special instructions before use. Ensure adequate ventilation. Do not breathe dust. Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice.
7.2. Conditions for safe storage,	Keep container tightly closed and dry. Store away from incompatible materials.

including any incompatibilities

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Limestone

OSHA	5 mg/m³ TWA (respirable fraction) 15 mg/m³ TWA (total dust)
ACGIH	10 mg/m³ Total Dust, 3 mg/m³ Respirable Dust
Canada	10 mg/m³
Canada - BC TWA	3 mg/m³ (respirable fraction); 10 mg/m³ (total dust)

Crystalline Silica, quartz (impurity)

OSHA	TWA: 0.05 mg/m³ OSHA Action level: 0.025 mg/m³
ACGIH	TWA: 0.025 mg/m³ respirable fraction
NIOSH	0.05 mg/m³ TWA (respirable dust)
Canada	0.025 mg/m³ TWA (respirable particulate)
Canada - BC TWA	0.025 mg/m³ TWA (respirable fraction)
Canada - Manitoba - OEL - TWA	0.025 mg/m³ TWA (respirable fraction)
Canada - Newfoundland & Labrador - OEL - TWA	0.025 mg/m³ TWA (respirable fraction)
Canada - Nova Scotia - OEL - TWA	0.025 mg/m³ TWA (respirable fraction)
Canada - Prince Edward Island - OEL - TWA	0.025 mg/m³ TWA (respirable fraction)
Mexico	0.1 mg/m³ TWA (respirable fraction)

Biological Limit Values: No information available

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC) No information available

8.2. Exposure controls

Engineering Measures Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

Personal protective equipment

Eye/Face Protection Wear safety glasses with side shields (or goggles).

Skin and Body Protection Wear suitable protective clothing.

Hand protection For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.

Hand Protection For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.

Respiratory Protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Thermal hazards	None known. Wear suitable protective clothing.
Hygiene Measures	Follow general hygiene considerations recognized as common good workplace practices. The worker should wash daily at the end of each work shift, and prior to eating, drinking, smoking, etc.
Environmental Exposure Controls	Dispose of in accordance with local regulations.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	
Physical State	Solid
Color	White
Odor	Odorless
Odor Threshold	No information available
pH:	8.4 - 10.2 5% Water suspension
Melting point / Freezing point	Not applicable
Boiling Point	Not applicable
Flash Point:	Not applicable.
Evaporation Rate	Not applicable.
Flammability (solid, gas)	Not applicable
Upper flammability limit:	
Lower flammability limit:	
Vapor Pressure	Not applicable
Vapor Density	Not applicable
Relative Density	2.7 g/cm3 @ 20°C
Water Solubility	1.3 g/l, 20° C
Solubility in other solvents	No information available
Partition coefficient	Not applicable
Autoignition Temperature	Not applicable
Decomposition Temperature	1292 - 1652 °F (700 - 900 °C)
Viscosity	Not applicable.
Explosive Properties	Not applicable
Oxidizing Properties	Not applicable

VOC Content (%)	Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity	None

10.2. Chemical stability	Stable
10.3. Possibility of hazardous reactions	No specific hazard known
10.4. Conditions to avoid	Incompatible materials
10.5. Incompatible materials	Strong acids
10.6. Hazardous decomposition products	None known

SECTION 11: Toxicological information

General Information Users are advised to consider national Occupational Exposure Limits or other equivalent values.

Information on Likely Routes of Exposure

Inhalation	Extended inhalation at levels above the workplace limit value can cause irreversible damage to the lungs (silicosis)
Skin	Contact with dust can cause mechanical irritation or drying of the skin
Eyes	Avoid contact with eyes Dust contact with the eyes can lead to mechanical irritation
Ingestion	Ingestion is not a likely route of exposure
Aspiration hazard	Not an expected route of exposure.
Symptoms related to the physical, chemical and toxicological characteristics	Contact with dust can cause mechanical irritation or drying of the skin. Dust may cause mechanical irritation to eyes. May cause irritation. Mucous Membrane. respiratory tract.

11.1. Information on toxicological effects

Limestone

Oral LD50	6450 mg/kg Rat

Crystalline Silica, quartz (impurity)

Oral LD50	500 mg/kg Rat Mouse
ACGIH	Group 2A - Probably Carcinogenic to Humans
IARC	Group 1 - Carcinogenic to Humans

Acute Toxicity Users are advised to consider national Occupational Exposure Limits or other equivalent values

Chronic Toxicity Potential occupational carcinogen.

Chronic Effects	Extended inhalation at levels above the workplace limit value can cause irreversible damage to the lungs (silicosis).
Respiratory Sensitization	Based on available data, the classification criteria are not met
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met
Skin Corrosion/Irritation	Based on available data, the classification criteria are not met
Skin Sensitization	Based on available data, the classification criteria are not met
Mutagenicity	Based on available data, the classification criteria are not met
Reproductive Effects	Based on available data, the classification criteria are not met.
Carcinogenicity	Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1).
Target Organ Effects	Respiratory system.
Specific target organ toxicity - Single exposure	No information available.
Specific target organ toxicity - Repeated exposure	May cause damage to organs through prolonged or repeated exposure if inhaled. Lungs.

SECTION 12: Ecological information

12.1. Ecotoxicity Not considered to be harmful to aquatic life.

Limestone
WGK Classification (VwVwS) 317 WGK: nwg
Crystalline Silica, quartz (impurity)
WGK Classification (VwVwS) 849 WGK: nwg

12.2. Persistence and degradability	Not readily biodegradable.
12.3. Bioaccumulative potential	None.
Partition coefficient	Not applicable
Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	None.

12.5. Results of PBT and vPvB assessment This substance does not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects None known

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal Methods Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Waste codes Waste codes should be assigned by the user based on the application for which the product was used

Limestone
European Waste Catalog 10130414
WGK Classification (VwVwS) 317 WGK: nwg
Crystalline Silica, quartz (impurity)
WGK Classification (VwVwS) 849 WGK: nwg

SECTION 14: Transport information

Mode of Transportation (Road, Water, Air, Rail)

TDG -Canada Not regulated
DOT Not regulated
IATA Not regulated
IMDG/IMO Not regulated
ICAO Not regulated

14.1. UN number None

14.2. UN proper shipping name None

14.3. Transport hazard class(es) None

14.4. Packing group None

14.5. Environmental hazards No

14.6. Special precautions for Not applicable

user

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable

SECTION 15: Regulatory information

Global Inventories

Pure substance/mixture Substance

Chemical Name	CAS Number	EC No	REACH registration number	Australia (AICS)	Canada (DSL)	China (IECSC)	Japan	S. Korea (KECL)	Mexico	New Zealand	Philippines (PICCS)	Taiwan	TSCA: United States
Limestone	1317-65-3	215-279-6	Exempt	Y	Y	Y	(1)-122(ENCS)(ISHL)	KE-21996	Y	Y	Y	Y	Y
Crystalline Silica, quartz (impurity)	14808-60-7	238-878-4	Exempt	Y	Y	Y	(1)-548(ENCS)(ISHL)	KE-29983	Y	Y	Y	Y	Y

Legend
X / Y: Complies - / N: Not Listed Exempt

US Federal Regulations

EPA

CERCLA

Limestone

CERCLA	Not Listed
SARA 311/312 Hazardous Categorization	Not Listed

Crystalline Silica, quartz (impurity)

CERCLA	Not Listed
SARA 304	Listed
SARA 313	Listed

SARA 311/312 Hazardous Categorization

Crystalline Silica, quartz (impurity)

Acute Health Hazard	Yes
Chronic Health Hazard	Yes

CWA (Clean Water Act)
Not listed

CAA (Clean Air Act)
Not listed

U.S. State Right-to-Know Regulations

Chemical Name	CAS Number	California Proposition 65	California CPR	Massachusetts	Minnesota	New Jersey	Pennsylvania
Limestone	1317-65-3			Y	Y		Y

Crystalline Silica, quartz (impurity)	14808-60-7	Y		Y	Y	Y	Y

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)
This product can expose you to crystalline silica, which is known to the State of California to cause cancer.

CANADA

WHMIS:
This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

Limestone
H350; H372
Crystalline Silica, quartz (impurity)
H350; H372

SECTION 16: Other information

Prepared by Huber Engineered Materials (HEM) Global Regulatory Affairs
regulatory.affairs@huber.com

Issue Date: 25/Apr/2019
Print Date: 26/Apr/2019

Revision Number: 1.3

Reason for Version OSHA (Occupational Safety and Health Administration of the US Department of Labor).

Training Advice Do not handle until all safety precautions have been read and understood.

Abbreviations and acronyms

International Agency for Research on Cancer (IARC)
International Air Transport Association (IATA)
International Maritime Dangerous Goods (IMDG)
International Uniform Chemical Information Database (IUCLID)
Workplace Hazardous Materials Information System (WHMIS) status and classification
EPA SARA Title III Section 312 (40 CFR 370) Hazard Classification
DOT (Department of Transportation)
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
TWA - Time-Weighted Average
Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA)
The Classification, Labeling and Packaging of Substances and Mixtures (CLP) Regulation (EC 1272/2008)
PPE - Personal Protection Equipment
NIOSH - National Institute for Occupational Safety and Health
TDG (Transport of Dangerous Goods) Canada
CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act)
Reportable Quantity (RQ) (RQ/% in mixture)
STEL - Short Term Exposure Limit
TLV® - Threshold Limit Value
Derived No Effect Level (DNEL)
SVHC: Substances of Very High Concern for Authorization:
Land transport (ADR/RID)
Biochemical oxygen demand (BOD)
Chemical oxygen demand (COD)
ICAO (air)
(IMDG) International Maritime Dangerous Goods
Positive Pressure Self-Contained Breathing Apparatus (SCBA)

Predicted No Effect Concentration (PNEC)
Globally Harmonized System (GHS)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet