



Hubercarb® Q60 - FSMA

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03 Canadian Workplace Hazardous Material Information System (WHMIS) 2015 Mexico NOM-018-STPS-2000; NOM-018-STPS-2015 GHS (Globally Harmonized System)

Issue Date 28/Oct/2022 Print Date 28/Oct/2022 Revision Number 1.3.1 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name: Hubercarb® Q60 - FSMA

Pure substance/mixture Substance

1.2. Relevant identified uses of the substance or mixture and uses advised against

- Recommended Use Filler Functional additive
- Uses advised against None known.
- 1.3. Details of the supplier of the safety data sheet

Company:	Huber Carbonates, LLC
	3100 Cumberland Boulevard, Suite 600
	Atlanta, GA 30339 USA

- Tel: +1 678 247-7300
- Internet www.hubermaterials.com
- E-mail hubermaterials@huber.com

1.4. Emergency telephone number

SECTION 2: Hazards identification

CHEMTREC: +1 800 424 9300 or International +1 703 527 3887

2.1. Classification of the substance or mixture

OSHA Regulatory Status	Carcinogenicity category 1A
GHS Classification	Carcinogenicity category 1A Specific target organ toxicity (STOT) - repeated exposure, category 1
Physical Hazards	Not classified

Safety Data Sheet Hubercarb® Q60 - FSMA

Issue Date 28/Oct/2022 Print Date 28/Oct/2022	Revision Number 1.3.1 Page 2 of 11
Health Hazards	Carcinogenicity category 1A Specific target organ toxicity (STOT) - repeated exposure, category 1 Respiratory system
Environmental Hazard	Not classified
2.2. Label elements	
Symbols/Pictograms	
Signal Word	Danger
Hazard Statements	H350 - May cause cancer H372 - Causes damage to organs through prolonged or repeated exposure
Precautionary Statements	
Prevention	Obtain special instructions before use Do not handle until all safety precautions have been read and understood Do not breathe dust Wash hands thoroughly after handling Do not eat, drink or smoke when using this product Wear protective gloves/protective clothing/eye protection/face protection
Response	Get medical advice/attention if you feel unwell
Storage	Store locked up
Disposal	Dispose of contents/containers in accordance with local regulations
Additional Information:	Not applicable.
Hazards not otherwise classifie (HNOC)	ed None known.

Hubercarb® Q60 - FSMA

Issue Date 28/Oct/2022 Print Date 28/Oct/2022 Revision Number 1.3.1 Page 3 of 11

SECTION 3: Composition/information on ingredients

Pure substance/mixture

Substance

Chemical Name	CAS Number	TSCA: United States	Canada (DSL)	Mexico	EU REACH registration number	OSHA Regulatory Status	WHMIS	Weight-%
Limestone	1317-65-3	A	Y (NDSL)	Y	Exempt	Not classified	H350; H372	97 - 100
Crystalline Silica, quartz (impurity)	14808-60-7	A	Y	Y	Exempt	Carcinogenicity category 1A	H350; H372	0.2 - 2

Legend

X / Y: Complies ; A: Active ; - / N: Exempt / Not Listed

SECTION 4: First aid measures

4.1. Description of first aid measures

General Advice	When in doubt or if symptoms are observed, get medical advice.
Eye Contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Skin Contact	Wash with plenty of soap and water.
Ingestion	Rinse mouth thoroughly with water.
Inhalation	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
Aspiration hazard	Not an expected route of exposure.
4.2. Most important symptoms and effects, both acute and delayed	Signs and symptoms may include coughing, gasping, choking and difficulty breathing.
4.3. Indication of any immediate medical attention and special treatment needed	• IF exposed or concerned: Get medical advice/attention. Treatment should be symptomatic and supportive. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray (fog). Foam. Dry chemical. Carbon dioxide (CO2).

HUBER

Safety Data Sheet

Hubercarb® Q60 - FSMA

Issue Date 28/Oct/2022 Print Date 28/Oct/2022 Revision Number 1.3.1 Page 4 of 11

Unsuitable Extinguishing Media None known.

5.2. Special hazards arising from the substance or mixture Do not breathe dust.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear a self-contained breathing apparatus and chemical protective clothing.

Fire-fighting measures

In case of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	Keep unauthorized personnel away. Use personal protection recommended in Section 8. Avoid dust formation. Ensure adequate ventilation.
For non-emergency personnel	Keep unauthorized personnel away.
For emergency responders	Keep unauthorized personnel away. Use personal protection recommended in Section 8.
6.2. Environmental precautions	Avoid runoff to waterways and sewers.
6.3. Methods and material for containment and cleaning up	Large Spill: Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect dust Small Spill: Vacuum or sweep material and place in a disposal container
6.4. Reference to other sections	Section 8: Exposure controls and personal protection. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Avoid exposure - obtain special instructions before use. Ensure adequate ventilation. Do not breathe dust. Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice.
7.2. Conditions for safe storage, including any incompatibilities	Keep container tightly closed and dry. Store away from incompatible materials.

Hubercarb® Q60 - FSMA

Issue Date 28/Oct/2022 Print Date 28/Oct/2022 Revision Number 1.3.1 Page 5 of 11

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Limestone

Limestone	
OSHA	5 mg/m³ TWA (respirable fraction) 15 mg/m³ TWA (total dust)
OSHA - Final PELs -TWA ACGIH	15 mg/m³ TWA 10 mg/m³ Total Dust, 3 mg/m³ Respirable Dust
Canada	10 mg/m ³
Canada - British Columbia - OEL-	20 mg/m ³
STELs	•
Crystalline Silica, quartz (impur	
OSHA	TWA: 0.05 mg/m ³ OSHA Action level: 0.025 mg/m ³
ACGIH	TWA: 0.025 mg/m ³ respirable fraction
Canada	0.025 mg/m ³ TWA (respirable particulate)
Canada - British Columbia - OEL -	ACGIH Category A2 - Suspected Human Carcinogen
Designated Substances Canada - Ontario - OEL - TWA EVs	IARC Category 1 - Human Carcinogen 0.10 mg/m ³
Canada - Manitoba - OEL - TWA	0.025 mg/m ³ TWA (respirable fraction)
Canada - Nova Scotia - OEL - TWA	0.025 mg/m ³ TWA (respirable fraction)
	- 0.025 mg/m ³ TWA (respirable fraction)
TWA Mexico	Mexican Carcinogen Category: A2 (Suspected Human Carcinogen)
	TWA (VLE-PPT): 0.025 mg/m ³ .
DNEC (Dradiated No Effect	No information available
PNEC (Predicted No Effect Concentration)	No information available
concentration	
DNEL (Derived No Effect Level)	No information available
Dielegiaal Limit Valuaa	No information available
Biological Limit Values	No information available
Biological Limit Values 8.2. Exposure controls	No information available
8.2. Exposure controls	
-	No information available Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
8.2. Exposure controls Engineering Measures	
8.2. Exposure controls Engineering Measures Personal protective equipment	Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
8.2. Exposure controls Engineering Measures	
8.2. Exposure controls Engineering Measures Personal protective equipment	Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
8.2. Exposure controls Engineering Measures Personal protective equipment Eye/Face Protection	Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear safety glasses with side shields (or goggles). Wear suitable protective clothing. For operations where prolonged or repeated skin contact may occur, impervious
8.2. Exposure controls Engineering Measures Personal protective equipment Eye/Face Protection Skin and Body Protection	Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear safety glasses with side shields (or goggles). Wear suitable protective clothing.
8.2. Exposure controls Engineering Measures Personal protective equipment Eye/Face Protection Skin and Body Protection	Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear safety glasses with side shields (or goggles). Wear suitable protective clothing. For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn. When workers are facing concentrations above the exposure limit they must use
8.2. Exposure controls Engineering Measures Personal protective equipment Eye/Face Protection Skin and Body Protection Hand Protection	Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear safety glasses with side shields (or goggles). Wear suitable protective clothing. For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.
8.2. Exposure controls Engineering Measures Personal protective equipment Eye/Face Protection Skin and Body Protection Hand Protection	Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear safety glasses with side shields (or goggles). Wear suitable protective clothing. For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn. When workers are facing concentrations above the exposure limit they must use
8.2. Exposure controls Engineering Measures Personal protective equipment Eye/Face Protection Skin and Body Protection Hand Protection Respiratory Protection	Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear safety glasses with side shields (or goggles). Wear suitable protective clothing. For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

HUBER

Safety Data Sheet

Hubercarb® Q60 - FSMA

Issue Date 28/Oct/2022 Print Date 28/Oct/2022

Revision Number 1.3.1 Page 6 of 11

practices. The worker should wash daily at the end of each work shift, and prior to eating, drinking, smoking, etc.

Environmental Exposure Controls Dispose of in accordance with local regulations.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	
Physical State	Solid
Color	White
Odor	Odorless
Odor Threshold	No information available
pH:	8.4 - 10.2 5% Water suspension
Melting point / Freezing point	Not applicable
Boiling Point	Not applicable
Flash Point	Not applicable
Evaporation Rate	Not applicable.
Flammability (solid, gas)	Not applicable
Upper flammability limit:	
Lower flammability limit:	
Vapor Pressure	Not applicable
Vapor Density	Not applicable
Relative Density	2.7 g/cm3 @ 20°C
Water Solubility	1.3 g/l, 20° C
Solubility in other solvents	No information available
Partition coefficient	Not applicable
Autoignition Temperature	Not applicable
Decomposition Temperature	1292 - 1652 °F (700 - 900 °C)
Viscosity	Not applicable.
Explosive Properties	Not applicable
Oxidizing Properties	Not applicable
VOC Content (%)	Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity	None
10.2. Chemical stability	Stable
10.3. Possibility of hazardous reactions	No specific hazard known
10.4. Conditions to avoid	Incompatible materials
10.5. Incompatible materials	Strong acids
10.6. Hazardous decomposition	None known

Hubercarb® Q60 - FSMA

Issue Date 28/Oct/2022 Print Date 28/Oct/2022

products

Revision Number 1.3.1 Page 7 of 11

SECTION 11: Toxicological information

General Information	Users are advised to consider national Occupational Exposure Limits or other equivalent values.
Information on Likely Routes of	Exposure
Inhalation	Extended inhalation at levels above the workplace limit value can cause irreversible damage to the lungs (silicosis)
Skin	Prolonged or repeated contact may dry skin and cause irritation
Eyes	Avoid contact with eyes Dust contact with the eyes can lead to mechanical irritation
Ingestion	Ingestion is not a likely route of exposure
Aspiration hazard	Not an expected route of exposure.
Symptoms related to the physical, chemical and toxicological characteristics	Contact with dust can cause mechanical irritation or drying of the skin. Dust may cause mechanical irritation to eyes. May cause irritation. Mucous Membrane. respiratory tract.
11.1. Information on toxicologic	al effects
Limestone Oral LD50	6450 mg/kg Rat
<u>Crystalline Silica, quartz (impur</u> LD50s and LC50s Oral LD50	ity) 500 mg/kg Oral LD50 Rat 500 mg/kg Rat Mouse
ACGIH IARC	Group 2A - Probably Carcinogenic to Humans Group 1 - Carcinogenic to Humans
Acute Toxicity	Users are advised to consider national Occupational Exposure Limits or other equivalent values
Chronic Toxicity	Potential occupational carcinogen.
Chronic Effects	Extended inhalation at levels above the workplace limit value can cause irreversible damage to the lungs (silicosis).
Respiratory Sensitization	Based on available data, the classification criteria are not met
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met

HUBER

Safety Data Sheet

Hubercarb® Q60 - FSMA

Issue Date 28/Oct/2022 Print Date 28/Oct/2022	Revision Number 1.3.1 Page 8 of 11
Skin Corrosion/Irritation	Based on available data, the classification criteria are not met
Skin Sensitization	Based on available data, the classification criteria are not met
Mutagenicity	Based on available data, the classification criteria are not met
Reproductive Effects	Based on available data, the classification criteria are not met.
Carcinogenicity	Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1).
Target Organ Effects	Respiratory system.
Specific target organ toxicity - Single exposure	No information available.
Specific target organ toxicity - Repeated exposure	May cause damage to organs through prolonged or repeated exposure if inhaled. Lungs.

SECTION 12: Ecological information

12.1. Ecotoxicity

Not considered to be harmful to aquatic life.

Limestone WGK Classification (AwSV) 317 WGK: nwg Crystalline Silica, quartz (impurity) WGK Classification (AwSV) 849 WGK: nwg

12.2. Persistence and Not readily biodegradable. **degradability**

12.3. Bioaccumulative potential None.

Partition coefficient Not applicable

Bioconcentration factor Not available. (BCF)

12.4. Mobility in soil None.

12.5. Results of PBT and vPvB This substance does not meet the criteria for classification as PBT or vPvB. assessment

12.6. Other adverse effects None known

SECTION 13: Disposal considerations

Hubercarb® Q60 - FSMA

Issue Date 28/Oct/2022 **Print Date** 28/Oct/2022 Revision Number 1.3.1 Page 9 of 11

13.1. Waste treatment methods

Disposal Methods	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
Waste codes	Waste codes should be assigned by the user based on the application for which the product was used
Limestone	
European Waste Catalog	10130414
WGK Classification (AwSV)	317 WGK: nwg
Crystalline Silica, quartz (impur	ity)

WGK Classification (AwSV) 849 WGK: nwg

SECTION 14: Transport information

Mode of Transportation (Road, Water, Air, Rail)

TDG -Canada	Not regulated
DOT	Not regulated
ΙΑΤΑ	Not regulated
IMDG/IMO	Not regulated
ICAO	Not regulated

14.1.	UN	number	None

- 14.2. UN proper shipping name None
- 14.3. Transport hazard class(es) None
- 14.4. Packing group None
- **14.5. Environmental hazards** No
- 14.6. Special precautions for Not applicable user

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

Hubercarb® Q60 - FSMA

Revision Number 1.3.1

Page 10 of 11

Issue Date 28/Oct/2022 Print Date 28/Oct/2022

Global Inventories

Pure substance/mixture Subs

Substance

Chemical Name	CAS Number	EC No	EU REACH registrati on number	Australia (AIIC)	Canada (DSL)	China (IECSC)	Japan	S. Korea (KECL)	Mexico		Philippine s (PICCS)	Taiwan	TSCA: United States
Limestone	1317-65-3	215-279-6	Exempt	Y	Y (NDSL)	Y	(1)-122(EN CS)(ISHL)	KE-21996	Y	Y	Y	Y	A
Crystalline Silica, quartz (impurity)		238-878-4	Exempt	Y	Y	Y	(1)-548(EN CS)(ISHL)	KE-29983	Y	Y	Y	Y	A

Legend

X / Y: Complies ; A: Active ; - / N: Exempt / Not Listed

US Federal Regulations

<u>EPA</u>

SARA 311/312 Hazardous Categorization Carcinogenicity

CWA (Clean Water Act) Not listed

CAA (Clean Air Act) Not listed

U.S. State Right-to-Know Regulations

Chemical Name	CAS Number	California Proposition 65	Massachusetts	Minnesota	New Jersey	Pennsylvania
Limestone	1317-65-3	N	Y	Y	sn 4001	Y
Crystalline Silica, quartz (impurity)	14808-60-7	Y	Y	Y	sn 1660	Y

Legend Y: Listed ; N: Not Listed

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)

This product can expose you to crystalline silica, which is known to the State of California to cause cancer.

CANADA

WHMIS

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

Limestone H350; H372 Crystalline Silica, quartz (impurity) H350; H372

SECTION 16: Other information

Huber Engineered Materials (HEM) Global Regulatory Affairs regulatory.affairs@huber.com

Safety Data Sheet Hubercarb® Q60 - FSMA

Revision Number 1.3.1

Page 11 of 11

Issue Date 28/Oct/2022 Print Date 28/Oct/2022

Issue Date Print Date	28/Oct/2022 28/Oct/2022
Revision Number	1.3.1
Reason for Version	OSHA (Occupational Safety and Health Administration of the US Department of Labor).
Training Advice	Do not handle until all safety precautions have been read and understood.
Abbreviations and acronyms	IARC (International Agency for Research on Cancer) IATA (International Air Transport Association) IMDG (International Maritime Dangerous Goods) IUCLID (International Uniform Chemical Information Database) WHMIS (Workplace Hazardous Materials Information Dystem) DOT (Department of Transportation) OSHA (Occupational Safety and Health Administration of the US Department of Labor) TWA (Time-Weighted Average) CLP (The Classification, Labeling and Packaging of Substances and Mixtures Regulation (EC 1272/2008)) PPE (Personal Protection Equipment) NIOSH (National Institute for Occupational Safety and Health) TDG (Transport of Dangerous Goods) Canada CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act) RQ (Reportable Quantity) (RQ/% in mixture) STEL (Short Term Exposure Limit) TLV® (Threshold Limit Value) DNEL (Derived No Effect Level) SVHC (Substances of Very High Concern) BOD (Biochemical oxygen demand) COD (Chemical oxygen demand) ICAO (International Maritime Dangerous Goods) ADR (European Agreement Concerning the International Carriage of Dangerous Goods by Road) RID (Agreement Concerning the International Carriage of Dangerous Goods by Road) RID (Agreement Concerning the International Carriage of Dangerous Goods by Road) RID (Agreement Concerning the International Carriage of Dangerous Goods by Road) RID (Agreement Concerning the International Carriage of Dangerous Goods by Road) RID (Agreement Concerning the International Carriage of Dangerous Goods by Road) RID (Agreement Concerning the International Carriage of Dangerous Goods by Road) RID (Agreement Concerning the International Carriage of Dangerous Goods by Road) RID (Agreement Concerning the International Carriage of Dangerous Goods by Road) RID (Agreement Concerning the International Carriage of Dangerous Goods by Road) RID (Agreement Concerning the International Carriage of Dangerous Goods by Road) RID (Agreement Concerning the International Carriage of Dangerous Goods by Road) RID (Agreement Concerning the International Carriage o
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet