Safety Data Sheet



ReCal® Pre-C 8

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03
Canadian Workplace Hazardous Material Information System (WHMIS) 2015
Mexico NOM-018-STPS-2000; NOM-018-STPS-2015
Globally Harmonized System (GHS)

Issue Date: 15/May/2019 Revision Number: 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name: ReCal® Pre-C 8

Pure substance/mixture Substance

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Filler. Functional additive.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company: Huber Carbonates, LLC

3100 Cumberland Boulevard, Suite 600

Atlanta, GA 30339 USA

Tel: +1 678 247-7300

Internet www.hubermaterials.com

E-mail hubermaterials@huber.com

1.4. Emergency telephone

number

CHEMTREC: +1 800 424 9300 or International +1 703 527 3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

OSHA Regulatory Status Carcinogenicity category 1A

Specific target organ toxicity (STOT) - repeated exposure, category 2

GHS Classification Carcinogenicity category 1A

Specific target organ toxicity (STOT) - repeated exposure, category 2

Safety Data Sheet

ReCal® Pre-C 8

Issue Date: 15/May/2019 **Revision Number: 1.3 Print Date:** 15/May/2019

Page 2 of 12

Physical Hazards Not classified

Health Hazards Carcinogenicity category 1A

Specific target organ toxicity (STOT) - repeated exposure, category 2

Respiratory system

Environmental Hazard Not classified

2.2. Label elements

Symbols/Pictograms



Signal Word Danger

Hazard Statements H350 - May cause cancer

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary Statements

Prevention Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust

Wear protective gloves/protective clothing/eye protection/face protection

IF exposed or concerned: Get medical advice/attention Response

Store locked up **Storage**

Disposal Dispose of contents/containers in accordance with local regulations

Additional Information: Not applicable.

Hazards not otherwise classified None known.

(HNOC)

Safety Data Sheet

ReCal® Pre-C 8

Issue Date: 15/May/2019 **Revision Number: 1.3**

Print Date: 15/May/2019 Page 3 of 12

SECTION 3: Composition/information on ingredients

Substance Pure substance/mixture

Chemical Name	CAS Number	TSCA: United States	Canada (DSL)	Mexico	REACH registration number	OSHA Regulatory Status	WHMIS	Weight-%
Limestone	1317-65-3	Υ	Υ	Υ	Exempt	Not classified	H350; H372	97 - 100
Crystalline Silica, quartz (impurity)	14808-60-7	Y	Y	Y	Exempt	Carcinogenicity category 1A Specific target organ toxicity (STOT) - repeated exposure, category 2	H350; H372	0.2 - 2

Legend

X / Y: Complies , - / N: Not Listed , Exempt

SECTION 4: First aid measures

4.1. Description of first aid measures

General Advice When in doubt or if symptoms are observed, get medical advice.

Eye Contact In case of eye contact, remove contact lens and rinse immediately with plenty of

water, also under the eyelids, for at least 15 minutes.

Skin Contact Wash with plenty of soap and water.

Rinse mouth thoroughly with water. Ingestion

Inhalation If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

Aspiration hazard Not an expected route of exposure.

4.2. Most important symptoms and effects, both acute and

delayed

Signs and symptoms may include coughing, gasping, choking and difficulty

breathing.

medical attention and special

treatment needed

4.3. Indication of any immediate IF exposed or concerned: Get medical advice/attention. Treatment should be symptomatic and supportive. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of

contamination.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Safety Data Sheet ReCal® Pre-C 8

Issue Date: 15/May/2019 Revision Number: 1.3

Print Date: 15/May/2019 **Page 4 of 12**

Suitable Extinguishing

Media

Water spray (fog). Foam. Dry chemical. Carbon dioxide (CO2).

Unsuitable Extinguishing Media

None known.

5.2. Special hazards arising from the substance or mixture

Do not breathe dust.

5.3. Advice for firefighters

Special protective

equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Fire-fighting measures

In case of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep unauthorized personnel away. Use personal protection recommended in Section 8. Avoid dust formation. Ensure adequate ventilation.

For non-emergency personnel Keep unauthorized personnel away.

For emergency responders Keep unauthorized personnel away. Use personal protection recommended in

Section 8.

6.2. Environmental precautions Avoid runoff to waterways and sewers.

6.3. Methods and material for containment and cleaning up

Large Spill: Do not dry sweep dust. Wet dust with water before sweeping or use a

vacuum to collect dust Small Spill: Vacuum or sweep material and place in a

disposal container

6.4. Reference to other sections Section 8: Exposure controls and personal protection. See Section 13 for

additional waste treatment information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid exposure - obtain special instructions before use. Ensure adequate ventilation. Do not breathe dust. Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, Keep container tightly closed and dry. Store away from incompatible materials.

Safety Data Sheet

ReCal® Pre-C 8

Issue Date: 15/May/2019 **Revision Number: 1.3 Print Date:** 15/May/2019

Page 5 of 12

including any incompatibilities

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Limestone

OSHA 5 mg/m³ TWA (respirable fraction)

15 mg/m³ TWA (total dust)

ACGIH 10 mg/m³ Total Dust, 3 mg/m³ Respirable Dust

Canada

Canada - BC TWA 3 mg/m³ (respirable fraction); 10 mg/m³ (total dust)

Crystalline Silica, quartz (impurity)

OSHA TWA: 0.05 ma/m³

OSHA Action level: 0.025 mg/m³ **ACGIH** TWA: 0.025 mg/m³ respirable fraction NIOSH 0.05 mg/m³ TWA (respirable dust) Canada 0.025 mg/m³ TWA (respirable particulate) Canada - BC TWA 0.025 mg/m³ TWA (respirable fraction) Canada - Manitoba - OEL - TWA 0.025 mg/m³ TWA (respirable fraction) Canada - Newfoundland & Labrador - 0.025 mg/m³ TWA (respirable fraction)

OFI - TWA

Canada - Nova Scotia - OEL - TWA 0.025 mg/m³ TWA (respirable fraction) Canada - Prince Edward Island - OEL - 0.025 mg/m3 TWA (respirable fraction)

T\//A

Mexico 0.1 mg/m3 TWA (respirable fraction)

Biological Limit Values: No information available

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC) No information available

8.2. Exposure controls

Provide a good standard of controlled ventilation (10 to 15 air changes per hour). **Engineering Measures**

Personal protective equipment

Wear safety glasses with side shields (or goggles). **Eye/Face Protection**

Skin and Body Protection Wear suitable protective clothing.

For operations where prolonged or repeated skin contact may occur, impervious Hand protection

gloves should be worn.

Hand Protection For operations where prolonged or repeated skin contact may occur, impervious

gloves should be worn.

Safety Data Sheet

ReCal® Pre-C 8

Issue Date: 15/May/2019 Revision Number: 1.3

Print Date: 15/May/2019 **Page 6 of 12**

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

Thermal hazards None known. Wear suitable protective clothing.

Hygiene Measures Follow general hygiene considerations recognized as common good workplace

practices. The worker should wash daily at the end of each work shift, and prior to

eating, drinking, smoking, etc.

Environmental Exposure

Controls

Dispose of in accordance with local regulations.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical State Solid
Color White
Odor Odorless

Odor Threshold No information available

pH: 8.4 - 10.2 5% Water suspension

Melting point / Freezing pointNot applicableBoiling PointNot applicableFlash Point:Not applicableEvaporation RateNot applicableFlammability (solid, gas)Not applicable

Upper flammability limit: Lower flammability limit:

Vapor PressureNot applicableVapor DensityNot applicableRelative Density2.7 g/cm3 @ 20°CWater Solubility1.3 g/l, 20° C

Solubility in other solvents No information available

Partition coefficientNot applicableAutoignition TemperatureNot applicable

Decomposition Temperature 1292 - 1652 °F (700 - 900 °C)

ViscosityNot applicable.Explosive PropertiesNot applicableOxidizing PropertiesNot applicable

VOC Content (%) Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

None

Safety Data Sheet ReCal® Pre-C 8

Revision Number: 1.3

Issue Date: 15/May/2019 Print Date: 15/May/2019 Page 7 of 12

Stable 10.2. Chemical stability

10.3. Possibility of hazardous

reactions

No specific hazard known

10.4. Conditions to avoid Incompatible materials

10.5. Incompatible materials Strong acids

10.6. Hazardous decomposition None known

products

SECTION 11: Toxicological information

General Information Users are advised to consider national Occupational Exposure Limits or other

equivalent values.

Information on Likely Routes of Exposure

Extended inhalation at levels above the workplace limit value can cause Inhalation

irreversible damage to the lungs (silicosis)

Skin Contact with dust can cause mechanical irritation or drying of the skin

Avoid contact with eyes Eyes

Dust contact with the eyes can lead to mechanical irritation

Ingestion is not a likely route of exposure Ingestion

Aspiration hazard Not an expected route of exposure.

Symptoms related to the

physical, chemical and

Contact with dust can cause mechanical irritation or drying of the skin. Dust may cause mechanical irritation to eyes. May cause irritation. Mucous Membrane.

toxicological characteristics respiratory tract.

11.1. Information on toxicological effects

Limestone

Oral LD50 6450 mg/kg Rat

Crystalline Silica, quartz (impurity)

Oral LD50 500 mg/kg Rat Mouse

ACGIH Group 2A - Probably Carcinogenic to Humans

Group 1 - Carcinogenic to Humans **IARC**

Acute Toxicity Users are advised to consider national Occupational Exposure Limits or other

equivalent values

Chronic Toxicity Potential occupational carcinogen.

Safety Data Sheet ReCal® Pre-C 8

Issue Date: 15/May/2019 Revision Number: 1.3

Print Date: 15/May/2019 **Page 8 of 12**

Chronic Effects Extended inhalation at levels above the workplace limit value can cause

irreversible damage to the lungs (silicosis).

Respiratory Sensitization Based on available data, the classification criteria are not met

Serious eye damage/eye

irritation

Based on available data, the classification criteria are not met

Skin Corrosion/Irritation Based on available data, the classification criteria are not met

Skin Sensitization Based on available data, the classification criteria are not met

Mutagenicity Based on available data, the classification criteria are not met

Reproductive Effects Based on available data, the classification criteria are not met.

Carcinogenicity Crystalline silica (quartz) has been classified by the International Agency for

Research on Cancer (IARC) as a known human carcinogen (Group 1).

Target Organ Effects Respiratory system.

Specific target organ toxicity -

Single exposure

No information available.

Specific target organ toxicity -

Repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Lungs.

SECTION 12: Ecological information

12.1. Ecotoxicity Not considered to be harmful to aquatic life.

Limestone

WGK Classification (VwVwS) 317 WGK: nwg

Crystalline Silica, quartz (impurity)

WGK Classification (VwVwS) 849 WGK: nwg

12.2. Persistence and

degradability

Not readily biodegradable.

12.3. Bioaccumulative potential None.

Partition coefficient Not applicable

Bioconcentration factor

(BCF)

Not available.

12.4. Mobility in soil None.

Safety Data Sheet

ReCal® Pre-C 8

Issue Date: 15/May/2019 **Revision Number: 1.3 Print Date:** 15/May/2019

Page 9 of 12

This substance does not meet the criteria for classification as PBT or vPvB. 12.5. Results of PBT and vPvB

assessment

12.6. Other adverse effects None known

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal Methods Disposal should be in accordance with applicable regional, national and local laws

and regulations.

Empty containers should be taken to an approved waste handling site for recycling **Contaminated Packaging**

or disposal.

Waste codes Waste codes should be assigned by the user based on the application for which

the product was used

Limestone

10130414 **European Waste Catalog** WGK Classification (VwVwS) 317 WGK: nwg

Crystalline Silica, quartz (impurity)

WGK Classification (VwVwS) 849 WGK: nwg

SECTION 14: Transport information

Mode of Transportation (Road, Water, Air, Rail)

Not regulated **TDG** -Canada Not regulated DOT Not regulated IATA IMDG/IMO Not regulated Not regulated **ICAO**

14.1. UN number None

14.2. UN proper shipping name None

14.3. Transport hazard class(es) None

14.4. Packing group None

14.5. Environmental hazards No

14.6. Special precautions for Not applicable

Safety Data Sheet

ReCal® Pre-C 8

Revision Number: 1.3 Issue Date: 15/May/2019 Print Date: 15/May/2019

Page 10 of 12

user

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

Global Inventories

Pure substance/mixture Substance

Chemical Name	CAS Number	EC No	REACH registrati on number	Australia (AICS)	Canada (DSL)	China (IECSC)	Japan	S. Korea (KECL)	Mexico	-	Philippine s (PICCS)		TSCA: United States
Limestone	1317-65-3	215-279-6	Exempt	Υ	Y	Y	(1)-122(EN CS)(ISHL)	KE-21996	Y	Y	Y	Υ	Y
Crystalline Silica, quartz (impurity)	14808-60- 7	238-878-4	Exempt	Y	Y	Y	(1)-548(EN CS)(ISHL)	KE-29983	Y	Y	Y	Y	Y

Legend

X / Y: Complies - / N: Not Listed Exempt

US Federal Regulations

EPA

CERCLA

Limestone

Not Listed **CERCLA** SARA 311/312 Hazardous Not Listed

Categorization Crystalline Silica, quartz (impurity)

CERCLA Not Listed **SARA 304** Listed **SARA 313** Listed

SARA 311/312 Hazardous Categorization

Crystalline Silica, quartz (impurity)

Acute Health Hazard Yes **Chronic Health Hazard** Yes

CWA (Clean Water Act)

Not listed

CAA (Clean Air Act)

Not listed

U.S. State Right-to-Know Regulations

	Chemical Name	CAS Number	California Proposition 65	California CPR	Massachusetts	Minnesota	New Jersey	Pennsylvania
ſ	Limestone	1317-65-3			Y	Y		Y

Safety Data Sheet

ReCal® Pre-C 8

Issue Date: 15/May/2019 **Revision Number: 1.3 Print Date:** 15/May/2019

Page 11 of 12

Crystalline Silica, quartz	14808-60-7	Y	Y	Y	Υ	Υ
(impurity)						

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)

This product can expose you to crystalline silica, which is known to the State of California to cause cancer.

CANADA

WHMIS:

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

Limestone

H350; H372

Crystalline Silica, quartz (impurity)

H350; H372

SECTION 16: Other information

Huber Engineered Materials (HEM) Global Regulatory Affairs Prepared by

regulatory.affairs@huber.com

15/May/2019 Issue Date: **Print Date:** 15/May/2019

Revision Number: 1.3

Reason for Version OSHA (Occupational Safety and Health Administration of the US Department of

Labor).

Do not handle until all safety precautions have been read and understood. **Training Advice**

International Agency for Research on Cancer (IARC) Abbreviations and acronyms

International Air Transport Association (IATA) International Maritime Dangerous Goods (IMDG)

International Uniform Chemical Information Database (IUCLID)

Workplace Hazardous Materials Information System (WHMIS) status and classification

EPA SARA Title III Section 312 (40 CFR 370) Hazard Classification

DOT (Department of Transportation)

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

TWA - Time-Weighted Average

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) The Classification, Labeling and Packaging of Substances and Mixtures (CLP) Regulation (EC 1272/2008)

PPE - Personal Protection Equipment

NIOSH - National Institute for Occupational Safety and Health

TDG (Transport of Dangerous Goods) Canada

CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act)

Reportable Quantity (RQ) (RQ/% in mixture)

STEL - Short Term Exposure Limit TLV® - Threshold Limit Value Derived No Effect Level (DNEL)

SVHC: Substances of Very High Concern for Authorization:

Land transport (ADR/RID)

Biochemical oxygen demand (BOD) Chemical oxygen demand (COD)

ICAO (air)

(IMDG) International Maritime Dangerous Goods

Positive Pressure Self-Contained Breathing Apparatus (SCBA)

Safety Data Sheet

ReCal® Pre-C 8

Issue Date: 15/May/2019 **Revision Number: 1.3** Print Date: 15/May/2019

Page 12 of 12

Predicted No Effect Concentration (PNEC) Globally Harmonized System (GHS)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet